







ECOLOGICAL PRODUCT

Wood composite is a durable and ecological alternative to hardwood.

It is made of a mix of wood flour and PVC.
Therefore it contributes to the protection and conservation of the tropical rain forests.

It does not require treatment with oil, solvents or cleaning products. The estimated life span exceeds that of conventional wood and afterwards is fully recyclable.



F. DUOFUSE ENG 03-2013

WOOD COMPOSITE

RANCH FENCING



SLAT WALL SYSTEM

A unique fencing system that combines design with durability.



TONGUE AND GROOVE BOARDS SYSTEM

The durable and modular alternative to hardwood garden fences.



DECKING

Enjoy a timeless and maintenance friendly decking.

Produced by PLASTIVAN

PLASTIVAN NV (Belgium)
Wantestraat 3 - B-8780 Oostrozebeke
T +32 56 66 75 51 - F +32 56 66 91 18
info@plastivan.com - www.plastivan.com

PLASTIVAN LTD (United Kingdom)
Unit 4 Bonville Industrial Estate Bonville Road
Brislington - Bristol BS4 5QU
T 0117 300 5625 - F 0117 971 5028
sales@plastivan.co.uk - www.plastivan.co.uk





The modular and durable alternative to hardwood or concrete ranch fencing.

DUOFUSE® WOOD COMPOSITE RANCH FENCING

ADVANTAGES WOOD COMPOSITE

- Ecological and recyclable.
- Easy to clean and to install.
- Slip resistant, brushed surface.
- Will not rot, swell, splinter or split.
- · Minimal discolouration, maintains original look.

ADVANTAGES RANCH FENCING

Stronger and more durable than wooden or concrete ranch fencing.

Versatile and modular:

- Heights possible up to 200cm. The number of boards and the space between the boards is free to choose.
- By using the corresponding U-profiles the boards can be attached to the post in 4 directions.
- Standard width of the boards is 180cm but boards can be cut to length.
- Can be used as fencing for (front) gardens, for grass-lands, for riding schools,...

ASSORTMENT AND DIMENSIONS

- Tropical Brown Stone Grey Graphite Black.
- Steel reinforced boards: 12 x 2.7 x 180cm.
- U-profile: 2.7 x 3.5 x 182 / 202cm.
- Spacer: 2.7 x 3.5 x 180cm.
- Internal post holder: for invisible fixing on concrete, terrace,...
- Cover cap to avoid water infiltration: 11 x 11 x 1.7cm.
- Composite post reinforced with an aluminium core: 9 x 9 x 270 / 300cm.
- The profiles should be screwed to the post using stainless steel screws.
 In between the boards a part of the spacer is clamped to create space between the boards.
- Guaranteed 10 years for all mechanical properties and resistant to all ant and insect attacks.

MAINTENANCE

Special cleaning products are not necessary. When the fencing has been exposed to some showers, water circles may occur. This is a temporary process. After some time this process stops it disappears completely. For normal maintenance a high pressure cleaner can be used (max. 80 bar) or just use normal domestic detergents.

For persistent dirt, use a diluted bleach solution. Do not use solvents!

For more information, technical details, warranty terms & conditions and installation details, see,

www.duofuse.com



The warmth and look of solid wood combined with the unique properties of plastic.





