

**DECLARATION OF PERFORMANCE
NO. 01/07/2013 PLV**

1. Unique identification code of the product type:
Hard PVC profile system for internal and external cladding and ceiling finishing
2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 11(4): 4:
Date of manufacture (batch number): see information label
3. Intended use or uses of the construction product in accordance with the applicable harmonised specification, as foreseen by the manufacturer:
Finishing of internal and external walls of residential, public utility and industrial buildings, for decorative purposes and in external wall insulation, roofline finishing.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer: as required pursuant to Article 11(5):

PLASTIVAN Sp. z o.o.	phone 61 815 57 47
ul. Główna 8	fax 61 815 5748
62-007 Biskupice	email: biuro@plastivan.pl
5. Where applicable, name and contact address of the authorised Representative whose mandate covers the tasks specified in Article 12 (2): 2:
Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System – 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
**PN EN 13245 -2:2009, PN EN 13245-1:2010, PN EN 13501-1
BUILDING RESEARCH INSTITUTE ITB BUILDING STRUCTURES DEPARTMENT
ACCREDITATION NO. AB 023 BUILDING RESEARCH INSTITUTE ITB FIRE
RESEARCH DEPARTMENT EJN NO. 1488**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable

9. Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical specification</i>
Vicat softening point	0.80	PN-EN ISO 306:2006
Flexural modulus	41	PN-EN ISO 178:2006
Thermal shrinkage at the temperature of 100°C	4	PN EN 479:1997
Durability of profiles for interior use	23,01	PN-EN 13245-1:2010
Durability of profiles for external use	23,01	PN-EN 13245-1:2010
Colour difference in laboratory conditions, irradiation GJ/m ²	A.2	PN-EN 513:2002
Reaction to fire classification	C-s3, d0	PN EN 13501-1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Biskupice. 01.07.2013

PLASTIVAN Sp. z o.o.
PRODUCTION MANAGER


Błażej Korzeniewski